Multiswitches

Cascadable multiswitches

SWI317..AS Series

17 input cascadable multiswitches
(16 SAT +1 TV)

- Isolation between outputs >30dB
- Cost effective
- Full HD compliant
- Bandwidth up to 2300 MHz
- Standard colour coding for easy installation

▶ **SWI317..S**

Item		SWI31706S	SWI31712S	SWI31716S
Code		289780	289781	289782
No. of inputs		17 (16 SAT + 1 TV)	17 (16 SAT + 1 TV)	17 (16 SAT + 1 TV)
No. of outputs		6	12	16
SAT				
Bandwidth	MHz	950-2300	950-2300	950-2300
Gain	dB	-3	-4	-5
Maximum output level	dBµV	100 (-35dBc 2 tones)	100 (-35dBc 2 tones)	100 (-35dBc 2 tones)
Insertion loss	dB	3	4	4
TV				
Bandwidth*	MHz	5-862	5-862	5-862
Gain	dB	-17	-21	-21
Insertion loss	dB	4	4	4
GENERAL PARAMETERS				
Switching control	V, KHz	14/18, 0/22 DiSEqC 2.0	14/18, 0/22 DiSEqC 2.0	14/18, 0/22 DiSEqC 2.0
Power consumption	mA	60	60	60
Dimensions (lxhxw)	mm	345x105x40	345x195x40	345x240x40
Operating temperature	°C	-20 to 60	-20 to 60	-20 to 60

*Return path included